



SPEAKER 82x82 mm.

8 ohm - 5/8W

P/N SPK820805

Test conditions of speaker + sound box:

1. Impedance	8Ω ± 15% at 1.0 KHz
2. Output S. P. L.	85 ± 2 dB (1.0 W/ 1.0 M) at 0.8, 1.0, 1.2, 1.5 KHz
3. Frequency Response	300 - 10K Hz (- 10dB based on Average S. P. L.)
4. Norminal Power	5.0 W
5. Maximum Power	8.0 W
6. Distortion Factor	Max. 10% at 600 Hz 1.0 W (2.0 V)
7. Load Test	White noise 24 hours at 8Ω, 5.0 W (6.32 V)
8. Operation Voltage	6.32 V by music program
9. Heat Test	+55 °C ± 2 °C 20% ~ 50% at 48 Hours
10. Cold Test	-25 °C ± 2 °C 20% ~ 50% at 48 Hours
11. Humidity	+40 °C ± 2 °C 90% ~ 95% at 96 Hours

Mechanical data:

1. Body materials	Black plastic ABS
2. Body dimensions	82 (L) x 82 (W) x 56 (T) mm
3. Front net	Coated black iron
4. Net weight	250 g
5. Support frame	Coated black steel
6. Cable	UL 2468 AWG22 x 2C (total length 2.0 M), Black color
7. Plug	3.5 mm Mono (90° head)
8. Logo printing	None
9. Instruction	None
10. Label	None