



DC COMPONENTS CO., LTD.

RECTIFIER SPECIALISTS

**BA157
THRU
BA159**

TECHNICAL SPECIFICATIONS OF FAST RECOVERY RECTIFIER

VOLTAGE RANGE - 400 to 1000 Volts

CURRENT - 1.0 Ampere

FEATURES

- * Fast switching
- * Low Iwakage
- * Low forward voltage drop
- * High current capability
- * High current surge
- * High reliability

MECHANICAL DATA


- * Case: Molded plastic
- * Epoxy: UL 94V-0 rated flame retardant
- * Lead: MIL-STD-202E, Method 208 guaranteed
- * Polarity: Color band denotes cathode end
- * Mounting position: Any
- * Weight: 0.33 gram approx.

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.



DO-41



Dimensions in inches and (millimeters)

	SYMBOL	BA157	BA158	BA159	UNITS
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	400	600	1000	Volts
Maximum RMS Voltage	V _{RMS}	280	420	700	Volts
Maximum DC Blocking Voltage	V _{dc}	400	600	1000	Volts
Maximum Average Forward Rectified Current at T _A = 55°C	I _o	1.0			Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	30			Amps
Maximum Instantaneous Forward Voltage at 1.0A DC	V _F	1.3			Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage T _A =25°C	I _R	5.0			μAmps
Maximum Full Load Reverse Current Average, Full Cycle .375"(9.5mm) lead length at T _L = 55°C		100			
Maximum Reverse Recovery Time (Note 1)	t _{rr}	150	250	500	nSec
Typical Junction Capacitance (Note 2)	C _J	15			pF
Operating and Storage Temperature Range	T _J , T _{STG}	-65 to +150			°C

NOTES : 1.Test Conditions: I_F = 0.5A, I_R = 1.0A, I_{RR} = 0.25A
2.Measured at 1 MHz and applied reverse voltage of 4.0 volts

RATING AND CHARACTERISTIC CURVES (BA157 THRU BA159)

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE





FIG. 6 - TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



DC COMPONENTS CO., LTD.