

DF - Modular



For 2 modules

Type: DF6B-UA/DF6B-LA
 Marking: A-B/a-b
 Number for modules: 2 modules
 Power side: 4~10mm²
 AWG: 12-8
 Signal side: 1~2.5mm²
 AWG: 18-14
 Matching: D6B-Hoods&Housings



For 3 modules

Type: DF10B-UA/DF10B-LA
 Marking: A-C/a-c
 Number for modules: 3 modules
 Power side: 4~10mm²
 AWG: 12-8
 Signal side: 1~2.5mm²
 AWG: 18-14
 Matching: D10B-Hoods&Housings



For 4 modules

Type: DF16B-UA/DF16B-LA
 Marking: A-D/a-d
 Number for modules: 4 modules
 Power side: 4~10mm²
 AWG: 12-8
 Signal side: 1~2.5mm²
 AWG: 18-14
 Matching: D16B-Hoods&Housings



For 6 modules

Type: DF24B-UA/DF24B-LA
 Marking: A-F/a-f
 Number for modules: 6 modules
 Power side: 4~10mm²
 AWG: 12-8
 Signal side: 1~2.5mm²
 AWG: 18-14
 Matching: D24B-Hoods&Housings

DM - Series



DMK-001-M



DMK-001-F

Terminal: Axial screw terminal
 Rated current: 200A
 Rated voltage: 1000V
 Wire gauge: 25~70mm²
 AWG: 2-0
 Poles: 1P
 Matching: DF6/10/16/24B-Frame



DMK-002-M



DMK-002-F

Terminal: Axial screw terminal
 Rated current: 100A
 Rated voltage: 1000V
 Wire gauge: 10~38mm²
 AWG: 6-2
 Poles: 2P
 Matching: DF6/10/16/24B-Frame



DMK-002-MC



DMK-002-FC

Terminal: Crimp terminal
 Rated current: 100A
 Rated voltage: 1000V
 Wire gauge: 10~35mm²
 MAX insulation diameter: 14
 Poles: 2P
 Matching: DF6/10/16/24B-Frame



DMK7-002-M



DMK7-002-F

Terminal: Axial screw terminal
 Rated current: 70A
 Rated voltage: 1000V
 Wire gauge: 6~22mm²
 AWG: 8-4
 Poles: 2P
 Matching: DF6/10/16/24B-Frame



DMK-002-M



DMK-002-F

Terminal: Axial screw terminal
 Rated current: 40A
 Rated voltage: 1000V
 Wire gauge: 2.5~10mm²
 AWG: 14-8
 Poles: 2P
 Matching: DF6/10/16/24B-Frame



DMK-002-MC



DMK-002-FC

Terminal: Crimp terminal
 Rated current: 40A
 Rated voltage: 1000V
 Wire gauge: 1.5~10mm²
 AWG: 16-8
 Poles: 2P
 Matching: DF6/10/16/24B-Frame



DMK-003-M



DMK-003-F

Terminal: Axial screw terminal
 Rated current: 40A
 Rated voltage: 690V
 Wire gauge: 2.5~10mm²
 AWG: 14-8
 Poles: 3P
 Matching: DF6/10/16/24B-Frame



DMK-003-MC



DMK-003-FC

Terminal: Crimp terminal
 Rated current: 40A
 Rated voltage: 500V
 Wire gauge: 1.5~10mm²
 AWG: 16-8
 Poles: 3P
 Matching: DF6/10/16/24B-Frame