



公差等级/General tolerances(mm)														
0	>3	>5	>10	>18	>30	>50	>80	>120	>180	>25	>31	>40	>50	0.1/10
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	0	
±0.1	±0.1	±0.2	±0.2	±0.3	±0.3	±0.5	±0.8	±0.9	±1.0	±1.1	±1.1	±1.6	±2.2	±2.5
2	8	2	6	1	7	7	0	3	5	5	0	0	0	±2'

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	/	/	/
IEC 标准/IEC Standard:	/	/	/
IEC 标准/IEC Standard:	/	/	/
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	/	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8	/	/
额定扭矩/Torque Tightening(N·m/Lbin)	M4, 1.54/14	/	/
线径范围(裸线/绞线)/Wire Range(rigid and flexible)(mm²/AWG)	0.5~10/20~6	/	/
厚度/Pitch(mm)	8.0	/	/
剥线长度/Stripping length(mm)	10~12	/	/
使用温度范围/Operating Temperature(°C)	-40~+105	/	/
符合RoHS标准/Conform to RoHS	Yes	/	/
标准颜色编号/Standard color number:	/	/	/
PANTONE / RAL	/	/	/

MATERIAL: / SURFACE: /

MAT NO.: /

STATUS: /

Appd: Li GL 2020.05.23

CHKD: Moo J 2020.05.23

DRFT:Wgng LX 2020.05.23

SIZE: A4

TYPE: CUSTOMER DRAWING

SCALE: 2:1

5	Grounding body	Copper alloy	Sn Plated
4	Cage	Steel	Zn Plated
3	Current carrier	Copper	Sn Plated
2	Screw	Steel	M4/Zn Plated
1	Housing	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES	REV	ECN	DESCRIPTION	DRFT	DATE
1								

NAME: DC10-PE-01P-1C-00A(H)

DRAWING NO.: DC10-PE-C01

REV: TO-2

SHEET: 1/1

NINGBO DEGSOIN ELECTRICAL CO., LTD

宁波高松电子有限公司