



公差等级/General Tolerances(mm)	
0	>3
~	>6
3	>10
6	>18
10	>30
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±0.93	±1.05
±1.15	±1.60
±2.20	±2.50
±Z	±Z

3	Cover	PC	UL94V-2
2	Metals	Steel	Sn plated
1	Housing	PC	UL94V-2
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准	UL Standard:	B	C
额定电压/电涌/Rated Voltage(V)/Current(A)	600/15	/	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	/	450/24	/
工频耐压/Withstanding Voltage(V/Min)	/	AC2500	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.5~2.5/22~14		
间距/Pitch(mm)/线数范围/Poles	3.5/05P		
铜线长度/Stripping length(mm)	10~13		
使用温度范围/Operating temperature(°C)	-40~+85		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL:	/
SURFACE:	/
MAT NO.:	/
STATUS:	/
APPD: LIGL	2020.06.03
CHKD: Mek	2020.06.03
DRT: LuoXM	2020.06.03
SIZE: A4	mm / inch
TYPE:	CUSTOMER DRAWING
SCALE:	2.5:1 SHEET
REV	T2
1/1	

DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD
 宁波高松电子有限公司

NAME: **DG228-3.5-05P-1Y-00A(H)**
 DRAWING NO.: DG228-3.5-C05

REV	ECN	DESCRIPTION	DRT	DATE
1				
2				
3				
4				
5				
6				