



- NOTES:
1. HOUSING MATERIAL: PBT UL94V-0, BALCK.
 2. CONTACTOR MATERIAL: FERROALLOY, NICKEL PLATED.
 3. CAGE MATERIAL: BRASS, TIN PLATED.
 4. SCREWS MATERIAL: M3.0, STEEL, ZINC PLATED.
- SPECIFICATIONS:
1. ELECTRICAL CHARACTERISTICS:
 - 1-1. RATING CURRENT: 30A
 - 1-2. VOLTAGE RATING: 750V
 - 1-3. CONTACT RESISTANCE: 20mΩ MAX.
 - 1-4. DIELECTRIC WITHSTANDING VOLTAGE: 3000V AC FOR ONE MINUTE.
 2. WIRE RANGE: 22~12AWG.
 3. SCREW TORQUE(N.m): M4/1.0.
 4. CONDUCTOR CROSS SECTION: 6MM².
 5. POLES: 2P~24P.
 6. AMBIENT TEMPERATURE RANGE: -40°C~+105°C.
 7. PART NO: MTTBOC-2 xx NBB-79A90

PIN NO.
(PER ROW)

I		linear dimension(Tolerances Standard GB/T 14486-2008)				—		□		⊥	
variable range	to	over	over	over	over	over	over	over	over	over	over
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60	

DIM	TOL	DEC	TOL
X.	±--	X.*	±--
X.X	±--	X.X*	±--
X.XX	±--	X.XX*	±--
X.XXX	±--	X.XXX*	±--



DEVETECH ELECTRONICS CO. LTD

DRWN: SAM	2019-02-16	PART NO.:	DV MTTBOC-2xxNBB-79A90
CHKD: ALAN	2019-02-16	TITLE:	14.0mm DUAL ROW BARRIER STRIP WASHER
APPD: WILLIAM	2019-02-16	DRAWING NO.:	DV MTTBOC-2xxNBB-79A90
SHEET: 1/1		UNIT	mm
		SCALE	N/A
		SIZE	A4
		REV	A