



33.3	29.2	52030-2810	28
31.3	27.2	-2610	26
29.3	25.2	-2410	24
27.3	23.2	-2210	22
17.3	13.2	-1210	12
15.3	11.2	-1010	10
13.3	9.2	-0810	8
11.3	7.2	-0610	6
9.3	5.2	52030-0410	4
B	A	ENG. NO.	種数 CKT.

注記:  
NOTES:  
△ CKT. NO. 1を基準に偶数番目のソルダーテール。  
EVEN NUMBER SOLDER TAIL.  
△ CKT. NO. 1を基準に奇数番目のソルダーテール。  
ODD NUMBER SOLDER TAIL.  
3. 材料:  
MATERIAL:  
ターミナル:リン青銅 銅メッキ(≒0.32)  
TERMINAL: PHOS-BRO.TIN-PLATED(≒0.32)  
ハウジング: 66ナイロン, UL94V-0  
HOUSING: 66NYLON, UL94V-0  
アクチュエーター: ポリエステル, UL94V-0  
ACTUATOR: POLYESTER, UL94V-0

REVISED EC NO: J2015-0012 DRAWN: YOSHII 2014/07/02 CHKD: YOKAYASHI 2014/07/02 APPR: YNOGAWA 2014/07/17	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE MM ONLY	SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
	10 UNDER ± ---	DRAWN BY FSATO	DATE 2013/07/12	TITLE 1.0 FPC CONN ZIF ST	
	10 OVER 30 UNDER ± ---	CHECKED BY KTAKAHASHI	DATE 2013/07/12		
	30 OVER ± ---	APPROVED BY YNOGAWA	DATE 2013/07/22		
ANGULAR ± --- °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE NOTES		DOCUMENT NO. SD-52030-021
A	SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		