





Outline Dimensions(Unit:mm)




Bobbin: UT-2001-1/PBT  
 Base: UT-2001/T375J  
 Core: UT20-H10K.  
 Wire: 2UEW-F.  
 Varnish: T4260GK

REV	DESCRIPTION	APPD	DATE



Electronical Schematic



Electrical Characteristics

Inductance : at 10KHz 0.1V.  
 L1-2=L4-3= 33.0 mH Min.  
 $|L1-L2| = 0.50$  mH Max.  
 D.C.Resistance : 1-2= 4-3= 2.00 ohms  $\pm 15\%$  .  
 Rated current: 0.30Amps Max.  
 Turns ratio : 1 : 1  $\pm 2\%$   
 Hi-Pot : pri-sec 1500VAC/2mA/3Second

No.286 RenMin East Road,Renheji Town,Tianchang city,Anhui province,China  
 TEL: :+86-550-7814888/7811988 FAX:+86-550-7831133  
 www.fuantronics.net

TOLERANCE LEVEL		天长市富安电子有限公司 Tianchang Fuan Electronic Co.,Ltd			
X.	—	DWN:	TITLE: UT20 common choke		
.X	$\pm 0.50$	Yuing.yu	FuAn P/N: FACM20V-333Y0R3		
.XX	$\pm 0.25$	CHKD:	Customer P/N: 33mH/0.3A		
.XXX	—	Benson.zhan	APPD:	Sheet	File No.
		Anson.zhan	1/1	1905044	Rev No. 1.0
					Date May./15/2019