


## FEATURE



1. Performing the text variations by LED colors.
2. Long operation life, above 1,000,000 times.
3. Sealed construction, dust-proof type.



## SPECIFICATIONS

CONTACT RATING: 50mA, 24VDC  
 OPERATION LIFE: 1,000,000 cycles  
 CONTACT RESISTANCE: 100mΩ max.(initial)  
 INSULATION RESISTANCE: 100MΩ min.  
 DIELECTRIC STRENGTH: 500VAC  
 OPERATING TEMPERATURE: -25°C to +70°C

## DIMENSION



## HOW TO ORDER

SPL — 10 —  —  —  /  —  —  —

Cap Size 10\*10

Operation Force

No. of LEDs

LED 1 color

LED 2 color

Cap Style and Content

RoHS code

- 1 = 100gf
- 2 = 160 gf
- 3 = 260 gf

- = Without LED
- 1 = 1
- 2 = 2

- = Without LED
- 1 = White
- 3 = Red
- 4 = Orange
- 5 = Yellow
- 6 = Green
- 7 = Blue

- = Without LED
- 1 = White
- 3 = Red
- 4 = Orange
- 5 = Yellow
- 6 = Green
- 7 = Blue

H = RoHS Compliant

No content

- 0 = Transparent
- 1 = White
- 2 = Black
- 3 = Red
- 5 = Yellow
- 6 = Green
- 7 = Blue
- M1 = Matte white cover (The Number is optional)

Have Text Combination

Text Combination	Color
F1 = " OFF "+ " ON "	36 37
F2 = " 切 "+ " 入 "	36 37
F4 = " X "+ " O "	36 37
F6 = " ↑ "	/
F7 = " △ "+ " △ "	36 37